

DP3 Pipelay Construction vessel

JASCON 25



Delivering the difference



DP3 Pipelay Construction vessel

Jascon 25 is a pipelay construction vessel built according to the Group's hybrid design philosophy featuring DP3, a large unobstructed main deck, a big crane, rigid/flexible pipelay capability and large scale offshore accommodation capacity.



Specifications

GENERAL

- **Classification**
ABS ✕ A1 Barge (E), ✕ PAS, ✕ DPS-3, CRC
- **Flag** Gibraltar
- **Call sign** ZDIS3
- **IMO number** 8770106
- **Delivered** February 2009

PRINCIPAL DIMENSIONS

- **Length overall** 118.80 m
- **Breadth** 30.40 m
- **Extreme breadth** 36.40 m
- **Depth** 8.40 m
- **Draft (max)** 4.98 m
- **Draft (max) including retr.** (3.10 m) thrusters 8.08 m

- **Gross tonnage** 14829 t
- **Net tonnage** 4638 t
- **Deadweight (summer)** 7867 t
- **Displacement (summer)** 16400 t

CRANAGE

- **Main crane (Huisman Itrec)**
800 mTon @ 30 m over the stern in sheltered waters and revolving at a radius of 26 m
- **Whiphoist** 120 mTon @ 33.50 m 3-fall config.
100 mTon @ 35.00 m 2-fall config.
50 mTon @ 72.00 m 2-fall config.
Heave compensation in 2 and single fall configuration
- **Auxiliary deck crane** Pedestal type,
34 t @ 20 m, 22 t @ 30 m, make TTS

DECK SPACE

- **Approx.** 800 - 1500 m²

DECK LOAD

- 10 t / m²

CAPACITIES

- **Fuel oil (storage)** 1887 m³
- **Fuel day tank (total)** 140 m³
- **Fuel overflow** 24 m³
- **Fuel purification** 81 m³
- **Lube oil** 89 m³
- **Fresh water (potable)** 2614 m³
- **Ballast water** 6955 m³
- **Sludge oil** 113 m³
- **Dirty oil** 81 m³
- **Black / Grey water** 516 m³
- **Bilge water** 170 m³

Specifications

SERVICE AIR

- 2 x DENO Compressors
- 24 m³ / min FAD at 6 bar

DP SYSTEM

- Kongsberg K-POS 22 aft working bridge
- Kongsberg K-POS 12 fwd navigation bridge

DP REFERENCE SYSTEMS

- 2 x Radius 1000 (independent separate) + transponders
- 2 x DGPS receivers
- 3 x Gyro compass
- 3 x Motion reference units
- 1 x Lightweight Tautwire
- 1 x HIPAP 500
- 1 x Gangway (if connected)
- 1 x Cyscan + Prisms clusters

POWER PLANT

- 4 x Caterpillar 3516 B diesel engines (1825 kW) each

PROPULSION

- **Bow thruster ROLLS ROYCE**
1 x electrically driven 1355 kW
- **Stern thrusters ROLLS ROYCE**
2 x FPP azimuth, 1920 kW each direct driven diesel
- **Forward/Aft thrusters ROLLS ROYCE**
4 x FPP retractable azimuth, 1920 kW each direct driven diesel

ENDURANCE

- **Freshwater making capacity**
2 x 50 t / 24 hrs
- **Fuel consumption (typical)**
 - In port 5 m³ / 24 hrs
 - Transit (2 x aft thrusters only) 20 m³ / 24 hrs
 - DP 15 m³ / 24 hrs

HELIDECK

- Suitable for Sikorsky S-92A Helibus
- Maximum "D" Value helideck 22.20 m
- Maximum take-off weight 13 t
- Helideck Monitoring System 100 Kongsberg
- Fixed foam system with 3 monitors

ACCOMMODATION

- 355 bunks in 105 cabins
 - 5 x 1 person cabins
 - 25 x 2 persons cabins
 - 75 x 4 persons cabins

Fully air-conditioned permanent accommodation for up to 355 bunks in cabins all with individual bathroom facilities. Including conference room, offices, cinema, gymnasium, recreation rooms, laundry, internet café as well as a medic room with hospital.

RADIO / COMMUNICATION

- V-Sat Standard bandwidth 512/256 kB
- GMDSS Area 3
- EPIRB
- SART
- Integrated Telephone System
- Sound Powered Telephone
- Public Address System

LIFESAVING APPLIANCES

- **Liferafts** 30 x 25 persons
- **Lifeboats** 4 x 106 persons
2 x 102 persons
- **Fast rescue boat** 1 x 6 persons

GANGWAY (OPTIONAL)

- **Max length** 42.50 m
- **Length in mid position** 36.50 m
- **Make** Marine Aluminium, Norway



PIPELAY EQUIPMENT (OPTIONAL)

- **Concept** Starboard mounted single joint S-lay system, make SAS, in dismantlable Firing Line shelter
- **Capacity** 4" - 48" diameter pipe (with coating 60")
- **Tensioners** 2 x tensioner of 60 t each
- **Davits** 5 x with load cells, capacity 60 t each
- **Stinger** length 55 m, supported by A-Frame
- **Workstations** Firing Line 3 welding stations, 1 NDE (X-ray or Ultrasonic) / repair station, 2 coating stations; all stations sheltered

(INSTALLED)

- **A&R system** A&R winch 120 t, make SAS

ADDITIONAL DATA

- **Sewage treatment unit** vacuum system, with nil overboard discharge, make EVAC
- **Incinerator** 800,000 kcal / hrs, make Teamtec
- **Yokohama fenders** 6.50 x 3.30 m



Sea Trucks Netherlands

Delftseplein 30M
P.O. Box 176
3000 AD Rotterdam
The Netherlands
T +31 10 75 40 100



Globally represented

Sea Trucks Group has offices in West Africa, Europe, Middle East, and Australia.

WEST AFRICA

- 1 Lagos, Nigeria**
Headquarters / Engineering & Operations office
- 2 Onne, Warri, Escravos, Nigeria**
Operational bases / Fabrication yard
- 3 Luanda, Angola**
Support office

EUROPE

- 4 Rotterdam, The Netherlands**
Engineering & Support office / Warehouse

MIDDLE EAST

- 5 Sharjah, U.A.E.**
Corporate Support office / Fabrication yard

ASIA PACIFIC

- 6 Perth, Australia**
Support office